

# **VSTR40DKX**

Sink material Stainless steel Type Monoblock bowl

No. of bowls

EAN code 8017709276805



### **Aesthetics**



**Aesthetic** Universale **Building in type** Undermount Series Mira Logo **Embossed** Colour Dark Inox Tap hole / precut tap No Taphole hole

**Finishing PVD** Brushed

	Bowl type	Bowl dimensions, WxDxH (mm)	Bowl depth (mm)	Radius corner bowl	Overflow	Strainer position	Strainer dimension
Bowl	Minimum radius	400 x 400 x 200	200	15	Yes, flush fitted	Wall position	3.5"

### **Technical Features**









**Characteristics PVD** coating

Coating thickness, Ecofriendly, Easy to clean, Hypoallergenic

200x440x440 mm

Tap hole diameter 35 mm No. of clips Type of clips Undermount clip

Dimensions of the

product (mm) **Cutout dimension** undermount (mm)

404\*404 mm

Base unit size

60 cm


## **Accessories Included**

**SMEG SPA** 19/5/2024



Accessories for installation

Strainer, Savespace siphon with dishwasher outlet connection, Fixing clips



SMEG SPA 19/5/2024



## Not included accessories



#### KITFD050

Waste disposal 0,5 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



#### DB34

St/steel drain basket to fit STD radius 340 x 400 bowl, 180 mm depth



#### KITFD100

Waste disposal 1 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



#### 3712

Siphon single bowl sinks (dishwasher connection included)



#### 3713

Siphon double bowls sinks (dishwasher connection included)



#### KITFD075

Waste disposal 0,75 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet

SMEG SPA 19/5/2024



## Symbols glossary (TT)



Cupboard width required for sink installation



Sink depth - depending on the model, the depth can be from 13 to 24,5



Under table top installation: The sink is fixed under tabletop, which extends the work surface and the depth of the sink.



Coating thickness between 0.2mm and 2mm



Easy to clean



The manufacturing process of PVD treatment is 100% green and eco-friendly



PVD coatings are hypoallergenic and suitable for use in contact with food

SMEG SPA 19/5/2024