

VSTR50BRX

Sink material Stainless steel Sink type Single-pressed bowl

No. of bowls 1

EAN code 8017709303020



Aesthetics



Aesthetics Universal **Building in type** Undermount Colour **Brass** Logo **Embossed Finishing PVD Brushed** Tap hole / precut tap No Taphole hole

Series Mira

_	Bowl type	Bowl dimensions, WxDxH (mm)	Bowl depth (mm)	Radius corner bowl	Overflow	Strainer position	Strainer dimension
Bowl	Minimum radius	500 x 400 x 200	200	15	Yes, flush fitted	Wall position	3.5"

Tap hole diameter

No. of clips

Type of clips

35 mm

Undermount clip

Technical Features









Characteristics composite material

Dimensions of the

Coating thickness, Ecofriendly, Pre-assembled gasket, Hypoallergenic

200x542x442 mm

product WxDxH (mm)

Cutout dimension undermount (mm) 404*504 mm


Base unit size 60 cm

Accessories Included



Accessories for installation

Strainer, Siphon with dishwasher outlet connection, Fixing clips





Compatible Accessories





Siphon single bowl sinks (dishwasher connection included)

3

3713

Siphon double bowls sinks (dishwasher connection included)



DB34

Cestello in filo inox per abbinamento alle vasche di dimensione 340*400 mm



KITFD050

Waste disposal 0,5 HP Motor: 1/2 horsepower Fits all sinks with 3 1/2" waste outlet



KITFD075

Waste disposal 0,75 HP Motor: 3/4 horsepower Fits all sinks with 3 1/2" waste outlet



KITFD100

Waste disposal 1 HP Motor: 1 horsepower Fits all sinks with 3 1/2" waste outlet



Alternative products



VSTR50CUX
Colour: Copper



VSTR50DKX
Colour: Gunmetal



Symbols glossary



Cupboard width required for sink installation



Sink depth - depending on the model, the depth can be from 13 to 24,5



Under table top installation: The sink is fixed under tabletop, which extends the work surface and the depth of the sink.




Easy to clean



Coating thickness between 0.2mm and 2mm



PVD coatings are hypoallergenic and suitable for use in contact with food





Benefit

One bowl

A single bowl for greater adaptability, capacity and space optimisation