

VSTR50CUX

Sink material Stainless steel Sink type Single-pressed bowl

No. of bowls 1

EAN code 8017709276850



Aesthetics



Aesthetics Universal Building in type Undermount Colour Copper Logo **Embossed Finishing PVD Brushed** Tap hole / precut tap No Taphole hole

Series Mira

Bowl depth Strainer Bowl Bowl dimensions, Radius Strainer Overflow type WxDxH (mm) (mm) corner bowl position dimension Minimum Yes, flush Wall 3.5" Bowl 500 x 400 x 200 200 15 radius fitted position

Tap hole diameter

No. of clips

Type of clips

35 mm

Undermount clip

Technical Features









Characteristics composite material Coating thickness, Ecofriendly, Pre-assembled gasket, Hypoallergenic 200x542x442 mm

Dimensions of the product WxDxH (mm)

Cutout dimension undermount (mm) 404*504 mm

Base unit size


60 cm

Accessories Included



Accessories for installation

Strainer, Siphon with dishwasher outlet connection, Fixing clips





Compatible Accessories





Siphon single bowl sinks (dishwasher connection included)

3713

Siphon double bowls sinks (dishwasher connection included)



DB34

Cestello in filo inox per abbinamento alle vasche di dimensione 340*400 mm



KITFD050

Waste disposal 0,5 HP Motor: 1/2 horsepower Fits all sinks with 3 1/2" waste outlet



KITFD075

Waste disposal 0,75 HP Motor: 3/4 horsepower Fits all sinks with 3 1/2" waste outlet



KITFD100

Waste disposal 1 HP Motor: 1 horsepower Fits all sinks with 3 1/2" waste outlet



Alternative products



VSTR50BRX Colour: Brass



VSTR50DKX

Colour: Gunmetal



Symbols glossary



Cupboard width required for sink installation



Sink depth - depending on the model, the depth can be from 13 to 24,5



Under table top installation: The sink is fixed under tabletop, which extends the work surface and the depth of the sink.




Easy to clean



Coating thickness between 0.2mm and 2mm



PVD coatings are hypoallergenic and suitable for use in contact with food





Benefit

One bowl

A single bowl for greater adaptability, capacity and space optimisation