

VZ45CT

Composite Sink material Composite bowl Type

No. of bowls

EAN code 8017709311711



Aesthetics

Aesthetic Universale On overflow Logo

Colour Cement / Concrete Alternative colours Black, White, Cream, Beige,

available EXTRA White, EXTRA Black Series Quadra

Tap hole / precut tap Prepared Building in type Standard hole

Bowl Bowl dimensions, Bowl depth Radius Strainer Strainer Overflow WxDxH (mm) corner bowl position dimension type (mm) Minimum Yes, Wall 400 x 400 x 210 3.5" Bowl 210 5 radius traditional position

Tap hole

No. of clips

Type of clips

Tap hole diameter

1

35 mm

Standard

Technical Features















Characteristics composite material

Antibacterial, Easy to clean, Anti-scratch, Termal schock resistant, High temperatures resistant,

Impact resistant, UV Resistant

Dimensions of the product (mm)

210x470x500 mm

Cutout dimension topmount (mm)

450 X 480 mm

Height from kitchen top

10 mm




Base unit size

45 cm

Accessories included

Accessories for installation

Strainer, Savespace siphon with dishwasher outlet connection, Fixing clips





Compatible Accessories

CB25MN



Single HPE chopping board to fit minimum radius bowls, black matt, measures 250 x 410 H 12 mm, dishwasher safe



COL19

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 26 mm



CB28QU

Single HPL chopping board for miminum radius, oak, measures 280 x 418 H 12 mm



COL19H

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 100 mm





Soap dispenser chrome finishing with square knob 40x40 mm

KITFD075



Waste disposal 0,75 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet

COL36



St/steel colander for MINIMUM radius bowls, measures 370 x 410 x 30 mm



KITFD050

Waste disposal 0,5 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



KITFD100

Waste disposal 1 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



Alternative products



VZ45N Colour: Black



VZ45B

Colour: White



Symbols glossary



Antibacterial



Cupboard width required for sink installation.



Standard installation: Traditional installation in tabletop, suitable for any kitchen sets.



High temperatures resistant



Termal schock resistant



Antiscratch



Sink depth - depending on the model, the depth can be from 13 to 24,5.



Easy to clean



Impact resistant



UV protection, does not fade over time.



Benefit (TT)

One bowl

A single bowl for greater adaptability, capacity and space optimisation

Tap hole possibility

Possibility of having the tap hole for direct installation of the tap on the sink, for a larger and neater surface area