

VZ45CT

Composite Sink material Composite bowl Type

No. of bowls

EAN code 8017709311711



Aesthetics



Universale **Aesthetic** On overflow Logo

Series Quadra Alternative colours

Black, White, Cream, Beige, available EXTRA White, EXTRA Black Colour Cement / Concrete

Building in type Standard

hole

Tap hole / precut tap Prepared

1

35 mm

Standard

Bowl Bowl dimensions, Bowl depth Radius Strainer Strainer Overflow WxDxH (mm) corner bowl position dimension type (mm) Minimum Yes, Wall 400 x 400 x 210 3.5" Bowl 210 5 radius traditional position

Tap hole

No. of clips

Type of clips

Tap hole diameter

Technical Features















Characteristics composite material

Antibacterial, Anti-scratch, Termal schock resistant, High temperatures

resistant, Impact resistant, Easy to clean, UV Resistant

210x470x500 mm

Dimensions of the

450 X 480 mm

Cutout dimension topmount (mm)

product (mm)

Height from kitchen top 10 mm Base unit size 45 cm


SMEG SPA 26/4/2024



Accessories Included

Accessories for installation

Strainer, Savespace siphon with dishwasher outlet connection, Fixing clips



SMEG SPA 26/4/2024



Not included accessories



KITFD050

Waste disposal 0,5 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



COL36

St/steel colander for MINIMUM radius bowls, measures 370 x 410 x 30 mm



KITFD100

Waste disposal 1 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



COL19H

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 100 mm



COL19

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 26 mm



KITDSQ

Soap dispenser chrome finishing with square knob 40x40 mm



CB25MN

Single HPE chopping board to fit minimum radius bowls, black matt, measures 250 x 410 H 12 mm, dishwasher safe



KITFD075

Waste disposal 0,75 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



CB28QU

Single HPL chopping board for miminum radius, oak, measures 280 x 418 H 12 mm

SMEG SPA 26/4/2024



Symbols glossary (TT)



Antibacterial



Cupboard width required for sink installation



Standard installation: Traditional installation in tabletop, suitable for any kitchen sets



High temperatures resistant



Easy to clean



Antiscratch



Sink depth - depending on the model, the depth can be from 13 to 24,5



Termal schock resistant



Impact resistant



UV protection, does not fade over time.

SMEG SPA 26/4/2024