

VZ57B

Sink material Composite Composite bowl Type

No. of bowls

EAN code 8017709183356



Aesthetics

Aesthetic Universale On overflow Logo

Alternative colours Black, Cream, Beige, Series Quadra available Cemento / Concrete, EXTRA Colour White White, EXTRA Black

Building in type Standard Prepared

Tap hole / precut tap hole

	Bowl type	Bowl dimensions, WxDxH (mm)	Bowl depth (mm)	Radius corner bowl	Overflow	Strainer position	Strainer dimension
Bowl	Minimum radius	500 x 400 x 210	210	5	Yes, traditional	Wall position	3.5"

Tap hole

No. of clips

Type of clips

Tap hole diameter

1

8

35 mm

Standard

Technical Features















Characteristics composite material

Antibacterial, Easy to clean, Anti-scratch, Termal schock resistant, High temperatures resistant, Impact resistant, UV

Resistant

210x570x500 mm

Dimensions of the product (mm)

topmount (mm)

Cutout dimension 550 X 480 mm

SMEG SPA 27/7/2024




Height from kitchen top 10 mm Base unit size 60 cm

Accessories Included

Accessories for installation

Strainer, Savespace siphon with dishwasher outlet connection, Fixing clips



SMEG SPA 27/7/2024



Not included accessories



KITFD050

Waste disposal 0,5 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



COL36

St/steel colander for MINIMUM radius bowls, measures 370 x 410 x 30 mm



KITFD100

Waste disposal 1 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



COL19H

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 100 mm



COL19

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 26 mm



KITDSQ

Soap dispenser chrome finishing with square knob 40x40 mm



CB25MN

Single HPE chopping board to fit minimum radius bowls, black matt, measures 250 x 410 H 12 mm, dishwasher safe



KITFD075

Waste disposal 0,75 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



CB28QU

Single HPL chopping board for miminum radius, oak, measures 280 x 418 H 12 mm

SMEG SPA 27/7/2024



Symbols glossary (TT)



Antibacterial



Cupboard width required for sink installation



Standard installation: Traditional installation in tabletop, suitable for any kitchen sets



High temperatures resistant



Easy to clean



Antiscratch



Sink depth - depending on the model, the depth can be from 13 to 24,5



Termal schock resistant



Impact resistant



UV protection, does not fade over time.

SMEG SPA 27/7/2024