

VZ57B

Sink material Composite Composite bowl Type

No. of bowls

EAN code 8017709183356



Aesthetics

Aesthetic Universale On overflow Logo

Alternative colours Black, Cream, Beige, Series Quadra available Cemento / Concrete, EXTRA Colour White White, EXTRA Black

Building in type Standard

Tap hole / precut tap Prepared hole

	Bowl type	Bowl dimensions, WxDxH (mm)	Bowl depth (mm)	Radius corner bowl	Overflow	Strainer position	Strainer dimension
Bowl	Minimum radius	500 x 400 x 210	210	5	Yes, traditional	Wall position	3.5"

Tap hole

No. of clips

Type of clips

Tap hole diameter

1

8

35 mm

Standard

Technical Features















Characteristics composite material

Antibacterial, Easy to clean, Anti-scratch, Termal schock resistant, High temperatures resistant, Impact resistant, UV

Resistant

Dimensions of the product (mm)

210x570x500 mm

Cutout dimension topmount (mm)

550 X 480 mm

SMEG SPA 26/7/2025




Height from kitchen top 10 mm Base unit size 60 cm

Accessories included

Accessories for installation

Strainer, Savespace siphon with dishwasher outlet connection, Fixing clips



SMEG SPA 26/7/2025



Compatible Accessories

CB25MN



Single HPE chopping board to fit minimum radius bowls, black matt, measures 250 x 410 H 12 mm, dishwasher safe

COL19

COL36

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 26 mm

St/steel colander for MINIMUM radius

bowls, measures 370 x 410 x 30 mm



miminum radius, oak, measures 280 x 418 H 12 mm

Single HPL chopping board for



COL19H

CB28QU

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 100 mm



KITDSQ

Soap dispenser chrome finishing with square knob 40x40 mm



KITFD050

Waste disposal 0,5 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



KITFD075

Waste disposal 0,75 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



KITFD100

Waste disposal 1 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet

SMEG SPA 26/7/2025



Symbols glossary



Antibacterial



Cupboard width required for sink installation



Standard installation: Traditional installation in tabletop, suitable for any kitchen sets



High temperatures resistant



Termal schock resistant



Antiscratch



Sink depth - depending on the model, the depth can be from 13 to 24,5



Easy to clean



Impact resistant



UV protection, does not fade over time.

SMEG SPA 26/7/2025



Benefit (TT)

One bowl

A single bowl for greater adaptability, capacity and space optimisation

Tap hole possibility

Possibility of having the tap hole for direct installation of the tap on the sink, for a larger and neater surface area

SMEG SPA 26/7/2025