

VZ79B

Sink material Composite Composite bowl Type

No. of bowls

EAN code 8017709183417



Aesthetics

Aesthetic Universale On overflow Logo

Alternative colours Black, Cream, Beige, Colour White available Cemento / Concrete, EXTRA Series Quadra

White, EXTRA Black Building in type Standard

Prepared

Tap hole / precut tap hole

	Bowl type	Bowl dimensions, WxDxH (mm)	Bowl depth (mm)	Radius corner bowl	Overflow	Strainer position	Strainer dimension
Bowl	Minimum radius	720 x 400 x 210	210	5	Yes, traditional	Wall position	3.5"

Tap hole

No. of clips

Type of clips

Tap hole diameter

1

10

35 mm

Standard

Technical Features















Characteristics composite material

Antibacterial, Easy to clean, Anti-scratch, Termal schock resistant, High temperatures resistant, Impact resistant, UV

Resistant

Dimensions of the product (mm)

210x790x500 mm

Cutout dimension topmount (mm)

770 X 480 mm




Height from kitchen top 10 mm Base unit size 80 cm

Accessories included

Accessories for installation

Strainer, Savespace siphon with dishwasher outlet connection, Fixing clips





Compatible Accessories

CB25MN



Single HPE chopping board to fit minimum radius bowls, black matt, measures 250 x 410 H 12 mm, dishwasher safe

COL19

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 26 mm



418 H 12 mm

CB28QU

COL19H St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 100 mm



COL36

St/steel colander for MINIMUM radius bowls, measures 370 x 410 x 30 mm



KITDSQ

Soap dispenser chrome finishing with square knob 40x40 mm

Single HPL chopping board for

miminum radius, oak, measures 280 x



KITFD050

Waste disposal 0,5 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



KITFD075

Waste disposal 0,75 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



KITFD100

Waste disposal 1 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet





Alternative products

VZ79CT

Colour: Cement / Concrete

VZ79N







Symbols glossary



Cupboard width required for sink installation.



Standard installation: Traditional installation in tabletop, suitable for any kitchen sets.



Antiscratch



High temperatures resistant



Easy to clean



Sink depth - depending on the model, the depth can be from 13 to 24,5.



Antibacterial



Termal schock resistant



Impact resistant



UV protection, does not fade over time.



Benefit (TT)

One bowl

A single bowl for greater adaptability, capacity and space optimisation

Tap hole possibility

Possibility of having the tap hole for direct installation of the tap on the sink, for a larger and neater surface area