

VZP45CT

Sink material Composite Composite bowl Type

No. of bowls

EAN code 8017709294120



Aesthetics





Aesthetic Universale On overflow Logo

Series Quadra Alternative colours Dove Gray, Black, White

available Colour Cement / Concrete

Tap hole / precut tap No Taphole Building in type Standard, Undermount

hole

6 mm

45, 50 cm

Standard + undermount clip

	Bowl type	Bowl dimensions, WxDxH (mm)	Bowl depth (mm)	Radius corner bowl	Overflow	Strainer position	Strainer dimension
Bowl	Minimum radius	400 x 400 x 215	215	10	Yes, flush fitted	Wall position	3.5"

Technical Features

















Characteristics composite material

Antibacterial, Easy to clean, Anti-scratch, Termal schock resistant, High temperatures resistant,

Impact resistant, UV

Resistant

Dimensions of the product (mm)

215x456x456 mm

Cutout dimension 446x446 mm topmount (mm)

Base unit size

No. of clips

Type of clips

Height from kitchen top

SMEG SPA 2025/07/25



Cutout dimension undermount (mm) Undermount cutout

radius


400x400 mm

10 mm

Accessories Included

Accessories for installation

Strainer, Savespace siphon with dishwasher outlet connection, Fixing clips



SMEG SPA 2025/07/25



Compatible Accessories

CB25MN



Single HPE chopping board to fit minimum radius bowls, black matt, measures 250 x 410 H 12 mm, dishwasher safe



COL19

COL36

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 26 mm

St/steel colander for MINIMUM radius

bowls, measures 370 x 410 x 30 mm



CB28QU

Single HPL chopping board for miminum radius, oak, measures 280 x 418 H 12 mm



COL19H

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 100 mm



KITDSQ

Soap dispenser chrome finishing with square knob 40x40 mm



KITFD050

Waste disposal 0,5 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



KITFD075

Waste disposal 0,75 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



KITFD100

Waste disposal 1 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet

SMEG SPA 2025/07/25



Symbols glossary



Antibacterial



Cupboard width required for sink installation



Standard installation: Traditional installation in tabletop, suitable for any kitchen sets



Cupboard width required for sink installation



High temperatures resistant



Easy to clean



Antiscratch



Sink depth - depending on the model, the depth can be from 13 to 24,5



Under table top installation: The sink is fixed under tabletop, which extends the work surface and the depth of the sink.



Termal schock resistant



Impact resistant



UV protection, does not fade over time.

SMEG SPA 2025/07/25



Benefit (TT)

One bowl

A single bowl for greater adaptability, capacity and space optimisation

SMEG SPA 2025/07/25