

VZP45CT

Sink material Composite Composite bowl Type

No. of bowls

EAN code 8017709294120



Aesthetics





Aesthetic

Series

Colour Cement / Concrete Building in type

Universale Quadra

Standard, Undermount

Logo

Alternative colours

available

Tap hole / precut tap

hole

On overflow

Dove Gray, Black, White

No Taphole

	Bowl type	Bowl dimensions, WxDxH (mm)	Bowl depth (mm)	Radius corner bowl	Overflow	Strainer position	Strainer dimension
Bowl	Minimum radius	400 x 400 x 215	215	10	Yes, flush fitted	Wall position	3.5"

Technical Features

















Characteristics composite material

Antibacterial, Easy to clean, Anti-scratch, Termal schock resistant, High temperatures resistant, Impact resistant, UV

Resistant

Dimensions of the product (mm)

215x456x456 mm

Cutout dimension topmount (mm)

446x446 mm

Height from kitchen top 6 mm 45, 50 cm Base unit size No. of clips

Type of clips Standard + undermount clip

SMEG SPA 8/8/2025



Cutout dimension undermount (mm) Undermount cutout

radius

400x400 mm


10 mm

.

Accessories included

Accessories for installation

Strainer, Savespace siphon with dishwasher outlet connection, Fixing clips



SMEG SPA 8/8/2025



Compatible Accessories

CB25MN



Single HPE chopping board to fit minimum radius bowls, black matt, measures 250 x 410 H 12 mm, dishwasher safe



COL19

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 26 mm



CB28QU

Single HPL chopping board for miminum radius, oak, measures 280 x 418 H 12 mm



COL19H

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 100 mm



St/steel colander for MINIMUM radius bowls, measures 370 x 410 x 30 mm



KITDSQ

Soap dispenser chrome finishing with square knob 40x40 mm



KITFD050

Waste disposal 0,5 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



KITFD075

Waste disposal 0,75 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



KITFD100

Waste disposal 1 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet

SMEG SPA 8/8/2025



Symbols glossary



Antibacterial



Cupboard width required for sink installation



Sink depth - depending on the model, the depth can be from 13 to 24,5



Under table top installation: The sink is fixed under tabletop, which extends the work surface and the depth of the sink.



High temperatures resistant



Termal schock resistant



Antiscratch



Cupboard width required for sink installation



Standard installation: Traditional installation in tabletop, suitable for any kitchen sets



Easy to clean



Impact resistant



UV protection, does not fade over time.

SMEG SPA 8/8/2025



Benefit (TT)

One bowl

A single bowl for greater adaptability, capacity and space optimisation

SMEG SPA 8/8/2025