

VZP45CT

Sink material	Composite
Type	Composite bowl
No. of bowls	1
EAN code	8017709294120



Aesthetics



Aesthetic	Universale	Logo	On overflow
Colour	Cement / Concrete	Alternative colours available	Dove Gray, Black, White
Series	Quadra		
Building in type	Standard, Undermount	Tap hole / precut tap hole	No Taphole

	Bowl type	Bowl dimensions, WxDxH (mm)	Bowl depth (mm)	Radius corner bowl	Overflow	Strainer position	Strainer dimension
Bowl	Minimum radius	400 x 400 x 215	215	10	Yes, flush fitted	Wall position	3.5"

Technical Features



Characteristics composite material	Antibacterial, Easy to clean, Anti-scratch, Thermal shock resistant, High temperatures resistant, Impact resistant, UV Resistant	Height from kitchen top	6 mm
		Base unit size	45, 50 cm
Dimensions of the product (mm)	215x456x456 mm	No. of clips	4
Cutout dimension topmount (mm)	446x446 mm	Type of clips	Standard + undermount clip

Cutout dimension 400x400 mm


undermount (mm)

Undermount cutout radius 10 mm

Accessories included

Accessories for installation

Strainer, Savespace siphon with dishwasher outlet connection, Fixing clips



Compatible Accessories

CB25MN



Single HPE chopping board to fit minimum radius bowls, black matt, measures 250 x 410 H 12 mm, dishwasher safe

COL19



St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 26 mm

COL36



St/steel colander for MINIMUM radius bowls, measures 370 x 410 x 30 mm

KITFD050



Waste disposal 0,5 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet

KITFD100

Waste disposal 1 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet

CB28QU



Single HPL chopping board for minimum radius, oak, measures 280 x 418 H 12 mm

COL19H



St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 100 mm



KITDSQ

Soap dispenser chrome finishing with square knob 40x40 mm



KITFD075

Waste disposal 0,75 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet

Alternative products



VZP45B

Colour: White



VZP45N

Colour: Black

Symbols glossary

	Antibacterial		Antiscratch
	Cupboard width required for sink installation.		Cupboard width required for sink installation
	Sink depth - depending on the model, the depth can be from 13 to 24,5.		Standard installation: Traditional installation in tabletop, suitable for any kitchen sets.
	Under table top installation: The sink is fixed under tabletop, which extends the work surface and the depth of the sink.		Easy to clean
	High temperatures resistant		Impact resistant
	Termal schock resistant		UV protection, does not fade over time.



Benefit (TT)

One bowl

A single bowl for greater adaptability, capacity and space optimisation