

VZP45N

Sink material Composite Composite bowl Type

No. of bowls

EAN code 8017709294137



Aesthetics





Aesthetic Universale On overflow Logo

Colour Black Alternative colours Dove Gray, White, Cemento

available / Concrete Series Quadra No Taphole

Tap hole / precut tap Building in type Standard, Undermount hole

	Bowl type	Bowl dimensions, WxDxH (mm)	Bowl depth (mm)	Radius corner bowl	Overflow	Strainer position	Strainer dimension
Bowl	Minimum radius	400 x 400 x 215	215	10	Yes, flush fitted	Wall position	3.5"

Technical Features

















Characteristics composite material

Antibacterial, Easy to clean, Anti-scratch, Termal schock resistant, High temperatures resistant,

Resistant

Dimensions of the product (mm)

215x456x456 mm

Cutout dimension topmount (mm)

446x446 mm

45, 50 cm Base unit size No. of clips Type of clips Standard + undermount clip Impact resistant, UV

Height from kitchen top

6 mm



Cutout dimension undermount (mm) Undermount cutout

radius


400x400 mm

10 mm

Accessories included

Accessories for installation

Strainer, Savespace siphon with dishwasher outlet connection, Fixing clips





Compatible Accessories

CB25MN



Single HPE chopping board to fit minimum radius bowls, black matt, measures 250 x 410 H 12 mm, dishwasher safe

COL19

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 26 mm



418 H 12 mm

CB28QU

COL19H St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 100 mm



COL36

St/steel colander for MINIMUM radius bowls, measures 370 x 410 x 30 mm



KITDSQ

Soap dispenser chrome finishing with square knob 40x40 mm

Single HPL chopping board for

miminum radius, oak, measures 280 x



KITFD050

Waste disposal 0,5 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



KITFD075

Waste disposal 0,75 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



KITFD100

Waste disposal 1 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



Alternative products



VZP45B
Colour: White



VZP45CT

Colour: Cement / Concrete



Symbols glossary



Cupboard width required for sink installation.



Standard installation: Traditional installation in tabletop, suitable for any kitchen sets.



Cupboard width required for sink installation



Antiscratch



High temperatures resistant



Easy to clean



Sink depth - depending on the model, the depth can be from 13 to 24,5.



Under table top installation: The sink is fixed under tabletop, which extends the work surface and the depth of the sink.



Antibacterial



Termal schock resistant



Impact resistant



UV protection, does not fade over time.



Benefit (TT)

One bowl

A single bowl for greater adaptability, capacity and space optimisation