

VZP56B

Sink material Composite Sink type Composite bowl

No. of bowls

EAN code 8017709294052



Aesthetics





Aesthetics Universal On overflow Logo

Alternative colours Colour White Dove Grey, Black, Cemento available

/ Concrete Series Quadra No Taphole

Building in type Standard, Undermount hole

Tap hole / precut tap

	Bowl type	Bowl dimensions, WxDxH (mm)	Bowl depth (mm)	Radius corner bowl	Overflow	Strainer position	Strainer dimension
Bowl	Minimum radius	500 x 400 x 215	215	10	Yes, flush fitted	Wall position	3.5"

Technical Features


















Strainer, Pre-assembled gasket, Siphon with dishwasher outlet connection, Siphon save space with dishwasher outlet connection, Fixing clips, Gasket, UV Resistant

Height from kitchen top Base unit size

No. of clips Type of clips 6 mm 60 cm

Standard + undermount clip

Dimensions of the product WxDxH (mm)

Cutout dimension (mm)

Cutout dimension undermount (mm) 546x446 mm 500x400 mm

215x556x456 mm




Cutout radius

10 mm

Accessories Included

Accessories for installation

Strainer, Siphon with dishwasher outlet connection, Fixing clips





Compatible Accessories

CB25MN



Single HPE chopping board to fit minimum radius bowls, black matt, measures 250 x 410 H 12 mm, dishwasher safe

COL19



St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 26 mm

St/steel colander for MINIMUM radius

bowls, measures 370 x 410 x 30 mm

Waste disposal 0,5 HP Motor: 1/2

horsepower Fits all sinks with 3 1/2"

COL36



418 H 12 mm

COL19H

CB28QU



St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 100 mm

miminum radius, oak, measures 280 x

Single HPL chopping board for

KITDSQ



Soap dispenser Square knob



KITFD100

waste outlet

KITFD050



Waste disposal 1 HP Motor: 1 horsepower Fits all sinks with 3 1/2" waste outlet

KITFD075

Waste disposal 0,75 HP Motor: 3/4 horsepower Fits all sinks with 3 1/2" waste outlet



Alternative products



VZP56N Colour: Black



VZP56CT
Colour: Grey



Symbols glossary



Antibacterial



Cupboard width required for sink installation



Standard installation: Traditional installation in tabletop, suitable for any kitchen sets



Easy to clean



Impact resistant



UV protection, does not fade over time.



Antiscratch



Sink depth - depending on the model, the depth can be from 13 to 24,5



Under table top installation: The sink is fixed under tabletop, which extends the work surface and the depth of the sink.



High temperatures resistant



Termal schock resistant



Benefit

One bowl

A single bowl for greater adaptability, capacity and space optimisation