

VZP56B

Sink material Composite Composite bowl Type

No. of bowls

EAN code 8017709294052



Aesthetics





Universale **Aesthetic** On overflow Logo

Series Quadra Alternative colours Dove Gray, Black, Cemento available

Colour White Tap hole / precut tap Building in type Standard, Undermount

hole

Height from kitchen top

Base unit size

No. of clips

Type of clips

/ Concrete

Standard + undermount clip

No Taphole

6 mm

60 cm

	Bowl type	Bowl dimensions, WxDxH (mm)	Bowl depth (mm)	Radius corner bowl	Overflow	Strainer position	Strainer dimension
Bowl	Minimum radius	500 x 400 x 215	215	10	Yes, flush fitted	Wall position	3.5"

Technical Features















Characteristics composite material

Antibacterial, Easy to clean, Anti-scratch, Termal schock resistant, High temperatures resistant,

Resistant

Dimensions of the product (mm)

215x556x456 mm

Impact resistant, UV

Cutout dimension topmount (mm)

546x446 mm

SMEG SPA 13/7/2025



Cutout dimension undermount (mm) Undermount cutout

radius


500x400 mm

10 mm

Accessories included

Accessories for installation

Strainer, Savespace siphon with dishwasher outlet connection, Fixing clips



SMEG SPA 13/7/2025



Compatible Accessories

CB25MN



Single HPE chopping board to fit minimum radius bowls, black matt, measures 250 x 410 H 12 mm, dishwasher safe

COL19



mm bowl, measures 200 x 410 x 26 mm

St/Steel colander to fit MINIMUM radius

COL19H

KITFD075

waste outlet

CB28QU

418 H 12 mm



St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 100 mm

miminum radius, oak, measures 280 x

Single HPL chopping board for

KITDSQ




COL36

St/steel colander for MINIMUM radius bowls, measures 370 x 410 x 30 mm


Soap dispenser chrome finishing with square knob 40x40 mm



KITFD100



Waste disposal 0,75 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2"





Waste disposal 1 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet

SMEG SPA 13/7/2025



Symbols glossary



Antibacterial



Cupboard width required for sink installation



Standard installation: Traditional installation in tabletop, suitable for any kitchen sets



Easy to clean



Termal schock resistant



UV protection, does not fade over time.



Antiscratch



Sink depth - depending on the model, the depth can be from 13 to 24,5



Under table top installation: The sink is fixed under tabletop, which extends the work surface and the depth of the sink.



High temperatures resistant



Impact resistant

SMEG SPA 13/7/2025



Benefit (TT)

One bowl

A single bowl for greater adaptability, capacity and space optimisation

SMEG SPA 13/7/2025