

VZP56N

Sink material Composite
Sink type Composite bowl

No. of bowls

EAN code 8017709294076



Aesthetics





Aesthetics Universal Logo On overflow

Colour Black Alternative colours Dove Grey, White, Cemento

Series Quadra available / Concrete

Building in type Standard, Undermount Tap hole / precut tap No Taphole hole

		Bowl type	Bowl dimensions, WxDxH (mm)	Bowl depth (mm)	Radius corner bowl	Overflow	Strainer position	Strainer dimension
ı	Bowl	Minimum radius	500 x 400 x 215	215	10	Yes, flush fitted	Wall position	3.5"

Technical Features















Characteristics composite material

Strainer, Pre-assembled gasket, Siphon with dishwasher outlet connection, Siphon save space with dishwasher outlet connection, Fixing clips, Gasket, UV Resistant

Base unit size No. of clips Type of clips

Height from kitchen top

4 Standard + undermount clip

6 mm

60 cm

Dimensions of the product WxDxH (mm)

Cutout dimension (mm)
Cutout dimension

undermount (mm)

546x446 mm 500x400 mm

215x556x456 mm




Cutout radius

10 mm

Accessories Included

Accessories for installation

Strainer, Siphon with dishwasher outlet connection, Fixing clips





Compatible Accessories

CB25MN



Single HPE chopping board to fit minimum radius bowls, black matt, measures 250 x 410 H 12 mm, dishwasher safe

COL19



St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 26 mm



COL19H

CB28QU

418 H 12 mm

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 100 mm

miminum radius, oak, measures 280 x

Single HPL chopping board for

COL36



St/steel colander for MINIMUM radius bowls, measures 370 x 410 x 30 mm

KITDSQ



Soap dispenser Square knob

KITFD050

Waste disposal 0,5 HP Motor: 1/2 horsepower Fits all sinks with 3 1/2" waste outlet

KITFD075



Waste disposal 0,75 HP Motor: 3/4 horsepower Fits all sinks with 3 1/2" waste outlet



KITFD100

Waste disposal 1 HP Motor: 1 horsepower Fits all sinks with 3 1/2" waste outlet



Alternative products



VZP56B
Colour: White



VZP56CT
Colour: Grey



Symbols glossary



Antibacterial



Cupboard width required for sink installation



Standard installation: Traditional installation in tabletop, suitable for any kitchen sets



Termal schock resistant



Impact resistant



UV protection, does not fade over time.



Antiscratch



Sink depth - depending on the model, the depth can be from 13 to 24,5



Under table top installation: The sink is fixed under tabletop, which extends the work surface and the depth of the sink.



High temperatures resistant



Easy to clean



Benefit

One bowl

A single bowl for greater adaptability, capacity and space optimisation