

VZP56N

Sink material Composite
Sink type Composite bowl

No. of bowls

EAN code 8017709294076



Aesthetics





Aesthetics Universal Logo On overflow

Series Quadra Alternative colours Dove Grey, White, Cemento
Colour Black available / Concrete

hole

Colour Black available / Concrete

Building in type Standard, Undermount Tap hole / precut tap No Taphole

Bowl dimensions, Bowl depth Radius Strainer Strainer Bowl Overflow WxDxH (mm) corner bowl dimension type (mm) position Yes, flush Minimum Wall 500 x 400 x 215 Bowl 215 10 3.5"

Technical Features

radius















Characteristics composite material

Strainer, Pre-assembled gasket, Siphon with dishwasher outlet connection, Siphon save space with dishwasher outlet connection, Fixing clips, Gasket, UV Resistant

Dimensions of the product WxDxH (mm)

Cutout dimension (mm)
Cutout dimension

undermount (mm)

546x446 mm 500x400 mm

215x556x456 mm

Height from kitchen top 6 mm
Base unit size 60 cm
No. of clips 4

fitted

Type of clips Standard + undermount clip

position




Cutout radius

10 mm

Accessories Included

Accessories for installation

Strainer, Siphon with dishwasher outlet connection, Fixing clips





Compatible Accessories





Single HPE chopping board to fit minimum radius bowls, black matt, measures 250 x 410 H 12 mm, dishwasher safe



COL19

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 26 mm



COL19H

418 H 12 mm

CB28QU

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 100 mm

miminum radius, oak, measures 280 x

Single HPL chopping board for





St/steel colander for MINIMUM radius bowls, measures 370 x 410 x 30 mm



KITDSQ

Soap dispenser Square knob



KITFD050

Waste disposal 0,5 HP Motor: 1/2 horsepower Fits all sinks with 3 1/2" waste outlet



KITFD075

Waste disposal 0,75 HP Motor: 3/4 horsepower Fits all sinks with 3 1/2" waste outlet



KITFD100

Waste disposal 1 HP Motor: 1 horsepower Fits all sinks with 3 1/2" waste outlet



Symbols glossary



Antibacterial



Cupboard width required for sink installation



Standard installation: Traditional installation in tabletop, suitable for any kitchen sets



Easy to clean



Impact resistant



UV protection, does not fade over time.



Antiscratch



Sink depth - depending on the model, the depth can be from 13 to 24,5



Under table top installation: The sink is fixed under tabletop, which extends the work surface and the depth of the sink.



High temperatures resistant



Termal schock resistant



Benefit

One bowl

A single bowl for greater adaptability, capacity and space optimisation