

VZP56N

Sink material Composite Type Composite bowl

No. of bowls

EAN code 8017709294076



Aesthetics





Universale **Aesthetic** Logo On overflow

Series Quadra Alternative colours Dove Gray, White, Cemento available / Concrete

Colour Black Tap hole / precut tap No Taphole Building in type Standard, Undermount

hole

6 mm

	Bowl type	Bowl dimensions, WxDxH (mm)	Bowl depth (mm)	Radius corner bowl	Overflow	Strainer position	Strainer dimension
Bowl	Minimum radius	500 x 400 x 215	215	10	Yes, flush fitted	Wall position	3.5"

Technical Features















Characteristics composite material

Antibacterial, Easy to clean, Anti-scratch, Termal schock resistant, High temperatures resistant,

Resistant

Dimensions of the product (mm)

215x556x456 mm

Cutout dimension topmount (mm)

546x446 mm

Base unit size 60 cm No. of clips Type of clips Standard + undermount clip Impact resistant, UV

Height from kitchen top

SMEG SPA 26/12/2024



Cutout dimension undermount (mm) Undermount cutout

radius


500x400 mm

10 mm

Accessories Included

Accessories for installation

Strainer, Savespace siphon with dishwasher outlet connection, Fixing clips



SMEG SPA 26/12/2024



Not included accessories



KITFD050

Waste disposal 0,5 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



KITFD100

Waste disposal 1 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



COL19

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 26 mm



CB25MN

Single HPE chopping board to fit minimum radius bowls, black matt, measures 250 x 410 H 12 mm, dishwasher safe



CB28QU

Single HPL chopping board for miminum radius, oak, measures 280 x 418 H 12 mm



COL36

St/steel colander for MINIMUM radius bowls, measures 370 x 410 x 30 mm



COL19H

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 100 mm



KITDSQ

Soap dispenser chrome finishing with square knob 40x40 mm



KITFD075

Waste disposal 0,75 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet

SMEG SPA 26/12/2024



Symbols glossary (TT)

3

Antibacterial



Cupboard width required for sink installation



Standard installation: Traditional installation in tabletop, suitable for any kitchen sets



Easy to clean



Termal schock resistant



UV protection, does not fade over time.



Antiscratch



Sink depth - depending on the model, the depth can be from 13 to 24,5



Under table top installation: The sink is fixed under tabletop, which extends the work surface and the depth of the sink.



High temperatures resistant



Impact resistant

SMEG SPA 26/12/2024