

VZP56N

Sink material	Composite
Type	Composite bowl
No. of bowls	1
EAN code	8017709294076



Aesthetics



Aesthetic	Universale	Logo	On overflow
Colour	Black	Alternative colours available	Dove Gray, White, Cemento / Concrete
Series	Qudra	Tap hole / precut tap hole	No Taphole
Building in type	Standard, Undermount		

	Bowl type	Bowl dimensions, WxDxH (mm)	Bowl depth (mm)	Radius corner bowl	Overflow	Strainer position	Strainer dimension
Bowl	Minimum radius	500 x 400 x 215	215	10	Yes, flush fitted	Wall position	3.5"

Technical Features



Characteristics composite material	Antibacterial, Easy to clean, Anti-scratch, Termal schock resistant, High temperatures resistant, Impact resistant, UV Resistant	Height from kitchen top	6 mm
		Base unit size	60 cm
		No. of clips	4
		Type of clips	Standard + undermount clip
Dimensions of the product (mm)	215x556x456 mm		
Cutout dimension topmount (mm)	546x446 mm		


Cutout dimension 500x400 mm

undermount (mm)

Undermount cutout 10 mm
radius

Accessories included

**Accessories for
installation** Strainer, Savespace siphon
with dishwasher outlet
connection, Fixing clips



Compatible Accessories

CB25MN



Single HPE chopping board to fit minimum radius bowls, black matt, measures 250 x 410 H 12 mm, dishwasher safe

COL19



St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 26 mm

COL36



St/steel colander for MINIMUM radius bowls, measures 370 x 410 x 30 mm

KITFD050



Waste disposal 0,5 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet

KITFD100



Waste disposal 1 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet

CB28QU



Single HPL chopping board for minimum radius, oak, measures 280 x 418 H 12 mm

COL19H



St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 100 mm



KITDSQ

Soap dispenser chrome finishing with square knob 40x40 mm



KITFD075

Waste disposal 0,75 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet

Alternative products



VZP56B

Colour: White



VZP56CT

Colour: Cement / Concrete

Symbols glossary

	Antibacterial		Antiscratch
	Cupboard width required for sink installation.		Sink depth - depending on the model, the depth can be from 13 to 24,5.
	Standard installation: Traditional installation in tabletop, suitable for any kitchen sets.		Under table top installation: The sink is fixed under tabletop, which extends the work surface and the depth of the sink.
	Termal schock resistant		High temperatures resistant
	Impact resistant		Easy to clean
	UV protection, does not fade over time.		



Benefit (TT)

One bowl

A single bowl for greater adaptability, capacity and space optimisation