

VZP76B

Sink material Composite Composite bowl Type

No. of bowls

EAN code 8017709294014



Aesthetics





Aesthetic Universale On overflow Logo

Colour White Alternative colours Dove Gray, Black, Cemento

available / Concrete Series Quadra No Taphole

Tap hole / precut tap Building in type Standard, Undermount hole

	Bowl type	Bowl dimensions, WxDxH (mm)	Bowl depth (mm)	Radius corner bowl	Overflow	Strainer position	Strainer dimension
Bowl	Minimum radius	700 x 400 x 215	215	10	Yes, flush fitted	Wall position	3.5"

Technical Features















Characteristics composite material

Antibacterial, Easy to clean, Anti-scratch, Termal schock resistant, High temperatures resistant, Impact resistant, UV

Resistant

Dimensions of the product (mm)

215x756x456 mm

Cutout dimension topmount (mm)

746x446 mm

Height from kitchen top 6 mm Base unit size 80 cm No. of clips Type of clips Standard + undermount clip



Cutout dimension undermount (mm)

700x400 mm


Undermount cutout radius

10 mm

Accessories included

Accessories for installation

Strainer, Savespace siphon with dishwasher outlet connection, Fixing clips





Compatible Accessories

CB25MN



Single HPE chopping board to fit minimum radius bowls, black matt, measures 250 x 410 H 12 mm, dishwasher safe



COL19

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 26 mm



CB28QU

Single HPL chopping board for miminum radius, oak, measures 280 x 418 H 12 mm



COL19H

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 100 mm

KITDSQ




Soap dispenser chrome finishing with square knob 40x40 mm

KITFD075



Waste disposal 0,75 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet

COL36





KITFD050

Waste disposal 0,5 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



KITFD100

Waste disposal 1 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



Alternative products

VZP76CT

Colour: Cement / Concrete



VZP76N

Colour: Black



Colour: Dove Gray





Symbols glossary



Antibacterial



Cupboard width required for sink installation.



Standard installation: Traditional installation in tabletop, suitable for any kitchen sets.



Termal schock resistant



Impact resistant



UV protection, does not fade over time.



Antiscratch



Sink depth - depending on the model, the depth can be from 13 to 24,5.



Under table top installation: The sink is fixed under tabletop, which extends the work surface and the depth of the sink.



High temperatures resistant



Easy to clean



Benefit (TT)

One bowl

A single bowl for greater adaptability, capacity and space optimisation