

WD1160

Product family	Thermodisinfectors
Type	Thermodisinfectors 60cm
Intrastat	90189084
EAN code	8017709184957



Technical Features

Undercounter installation	Yes	Emergency opening system	Yes
Washing levels	up to 4	Temperature sensors in Tank	2 x PT 1000 Class B IEC 60751
DIN loading capacity	up to 8	Noise level (dbA)	Max. 50 dBA
Door	1, balanced swing door in stainless steel	Serial RS232 port	Yes
Safety Door Lock	Yes, with electromagnetic release and automatic opening		

Programs

Standard programs stores	9	Program editing	Yes
Modifiable programs	6		

Interface

Electronic control	Yes	Remaining duration display	Yes
Display	LCD	Traceability	Last 250 executed programs
Set of display languages		Cycle Archive	Yes
Programme progress indicator	Yes	Download cycle	Optional, through LAN port, Yes, through RS232 port
End of cycle indicator	Yes	Diagnosis	Remote control with optional; With software
Alarm indicator	Yes, on the display	LAN connection	Optional

Construction

Washer Chamber Material	Stainless steel AISI 316L	Capacity washing chamber (gross volume)	168 l
External material of the machine	Stainless Steel AISI 304		

Equipments

Built-in water softener	Yes	Chemicals dosing	Standard
Steam Condenser	Yes	Water supply pipe	3/4"
Peristaltic pump for liquid detergent dosage	Yes	Supply pipe diameter	1/2"
Neutralizing peristaltic pump	Yes		

Electrical Connection

Electrical connection	3N AC 400V - 50Hz	Monophase conversion	Yes
Voltage (V)	400 V	Availability monophase version	Yes, optional
Plug	Not present	60 Hz Possibility	Yes, on demand
Frequency (Hz)	50 Hz		

Logistic Information

Dimensions of the product WxDxH (mm)	600x600x850	Gross weight (kg)	80,000 kg
Width (mm)	600 mm	Net weight	68,000 kg

Compatible Accessories



CSK4B



CSK6B



CSK8B