

Productkaart volgens de Gedelegeerde Verordening (EU) nr. 65/2014 van de Commissie van 1 oktober 2013 en de Gedelegeerde Verordening (EU) nr. 66/2014 van de Commissie van 14 januari 2014

Naam of handelsmerk van de leverancier	SMEG
Productcode	KAT1200HXE
Jaarlijks energieverbruik (AEChood)	58.2 kWh/a
Energy efficiency class	B
Fluid Dynamic Efficiency (FDEhood)	28
Fluid Dynamic Efficiency class	B
Lighting Efficiency (LEhood)	29 lux/W
Lighting Efficiency Class	A
Grease Filtering Efficiency	66 %
Grease Filtering Efficiency Class	D
Air Flow at minimum speed	240 m³/h
Air flow at maximum speed	448 m³/h
Air flow at boost speed	603 m³/h
Airbourne acoustical A-weighted sound Power Emission at minimum speed	46 dBA
Airborne acoustical A-weighted sound Power Emission at maximum speed	62 dBA
Airbourne acoustical A-weighted sound power emission at boost speed	69 dBA
Power consumption in stand-by mode	0.49 W
Time increase factor	1.00
Measured air flow rate at best efficiency point	336 m³/h
Measured air pressure at best efficiency point	434 Pa
Measured electric power input at best efficiency point	145 W
Normal Power of the light system	8 W
Gemiddelde lichtsterkte van het licht op het kookoppervlak (Emiddle)	218 lux
Sound power level at highest setting	62 dBA

19 de abril de 2025
