

**Product fiche concerning the COMMISSION REGULATION (EU) No 66/2014 of 14 January 2014**

---

Supplier name or brand	SMEG
Product code	KI120XE
Annual Efficiency Consumption (AEC <sub>hood</sub> )	63.6 kWh/a
Energy efficiency class	B
Fluid Dynamic Efficiency (FDE <sub>hood</sub> )	28.7
Fluid Dynamic Efficiency class	A
Lighting Efficiency (LE <sub>hood</sub> )	70.9 lux/W
Lighting Efficiency Class	A
Grease Filtering Efficiency	79.8 %
Grease Filtering Efficiency Class	C
Air Flow at minimum speed	316 m <sup>3</sup> /h
Air flow at maximum speed	529 m <sup>3</sup> /h
Air flow at boost speed	783 m <sup>3</sup> /h
Airbourne acoustical A-weighted sound Power Emission at minimum speed	48 dBA
Airborne acoustical A-weighted sound Power Emission at maximum speed	62 dBA
Airbourne acoustical A-weighted sound power emission at boost speed	70 dBA
Power Consumption in Off mode	0.71 W
Time increase factor	1.00
Energy efficiency index	58.7
Measured air flow rate at best efficiency point	394 m <sup>3</sup> /h
Measured air pressure at best efficiency point	449 Pa
Measured electric power input at best efficiency point	171 W
Normal Power of the light system	4 W
Average illumination of the light on the cooking surface (E <sub>middle</sub> )	312 lux
Sound power level at highest setting	62 dBA

Wednesday, 3 September 2025

---