

Produktblad angående KOMMISSIONENS DELEGERADE FÖRORDNING (EU) nr 65/2014 av den 1 oktober 2013 och KOMMISSIONENS DELEGERADE FÖRORDNING (EU) nr 66/2014 av den 14 januari 2014

Leverantörens namn eller varumärke	SMEG
Produktkod	KSDD90VN-2
Årlig effektförbrukning (AEC _{hood})	53 kWh/a
Energy efficiency class	A
Fluid Dynamic Efficiency (FDE _{hood})	30.5
Fluid Dynamic Efficiency class	A
Lighting Efficiency (LE _{hood})	40.2 lux/W
Lighting Efficiency Class	A
Grease Filtering Efficiency	38.9 %
Grease Filtering Efficiency Class	G
Air Flow at minimum speed	230 m ³ /h
Air flow at maximum speed	500 m ³ /h
Air flow at boost speed	730 m ³ /h
Airbourne acoustical A-weighted sound Power Emission at minimum speed	42 dB(A)
Airborne acoustical A-weighted sound Power Emission at maximum speed	59 dB(A)
Airbourne acoustical A-weighted sound power emission at boost speed	66 dB(A)
Time increase factor	1.00
Energy efficiency index	53.1
Measured air flow rate at best efficiency point	349 m ³ /h
Measured air pressure at best efficiency point	464 Pa
Measured electric power input at best efficiency point	147 W
Normal Power of the light system	6 W
Average illumination of the light on the cooking surface (E _{middle})	253 lux
Sound power level at highest setting	59 dB(A)

den 24 februari 2021
