

Product fiche concerning the COMMISSION REGULATION (EU) No 66/2014 of 14 January 2014

| | |
|---|-----------------------|
| Supplier name or brand | SMEG |
| Product code | KSGT124X |
| Annual Efficiency Consumption (AEC _{hood}) | 46.7 kWh/a |
| Energy efficiency class | A |
| Fluid Dynamic Efficiency (FDE _{hood}) | 33.1 |
| Fluid Dynamic Efficiency class | A |
| Lighting Efficiency (LE _{hood}) | 31.7 lux/W |
| Lighting Efficiency Class | A |
| Grease Filtering Efficiency | 91.4 % |
| Grease Filtering Efficiency Class | B |
| Air Flow at minimum speed | 223 m ³ /h |
| Air flow at maximum speed | 554 m ³ /h |
| Air flow at boost speed | 721 m ³ /h |
| Airbourne acoustical A-weighted sound Power Emission at minimum speed | 47 dBA |
| Airborne acoustical A-weighted sound Power Emission at maximum speed | 67 dBA |
| Airbourne acoustical A-weighted sound power emission at boost speed | 70 dBA |
| Power consumption in stand-by mode | 0.49 W |
| Time increase factor | 0.9 |
| Energy efficiency index | 46.7 |
| Measured air flow rate at best efficiency point | 355 m ³ /h |
| Measured air pressure at best efficiency point | 471 Pa |
| Measured electric power input at best efficiency point | 140 W |
| Normal Power of the light system | 5 W |
| Average illumination of the light on the cooking surface (E _{middle}) | 146 lux |
| Sound power level at highest setting | 67 dBA |

Saturday 23 May 2026