

**Product fiche concerning the COMMISSION REGULATION (EU) No 66/2014 of 14 January 2014**

---

Supplier name or brand	SMEG
Product code	KSGT124X
Annual Efficiency Consumption (AEC <sub>hood</sub> )	46.7 kWh/a
Energy efficiency class	A
Fluid Dynamic Efficiency (FDE <sub>hood</sub> )	33.1
Fluid Dynamic Efficiency class	A
Lighting Efficiency (LE <sub>hood</sub> )	31.7 lux/W
Lighting Efficiency Class	A
Grease Filtering Efficiency	91.4 %
Grease Filtering Efficiency Class	B
Air Flow at minimum speed	223 m <sup>3</sup> /h
Air flow at maximum speed	554 m <sup>3</sup> /h
Air flow at boost speed	721 m <sup>3</sup> /h
Airbourne acoustical A-weighted sound Power Emission at minimum speed	47 dBA
Airborne acoustical A-weighted sound Power Emission at maximum speed	67 dBA
Airbourne acoustical A-weighted sound power emission at boost speed	70 dBA
Power consumption in stand-by mode	0.49 W
Time increase factor	0.9
Energy efficiency index	46.7
Measured air flow rate at best efficiency point	355 m <sup>3</sup> /h
Measured air pressure at best efficiency point	471 Pa
Measured electric power input at best efficiency point	140 W
Normal Power of the light system	5 W
Average illumination of the light on the cooking surface (E <sub>middle</sub> )	146 lux
Sound power level at highest setting	67 dBA

Friday, 20 February 2026

---