

Productkaart volgens de Gedelegeerde Verordening (EU) nr. 65/2014 van de Commissie van 1 oktober 2013 en de Gedelegeerde Verordening (EU) nr. 66/2014 van de Commissie van 14 januari 2014

Naam of handelsmerk van de leverancier	SMEG
Productcode	KSGT64X
Jaarlijks energieverbruik (AEChood)	51.7 kWh/a
Energy efficiency class	B
Fluid Dynamic Efficiency (FDEhood)	29.0
Fluid Dynamic Efficiency class	A
Lighting Efficiency (LEhood)	78.5 lux/W
Lighting Efficiency Class	A
Grease Filtering Efficiency	72.0 %
Grease Filtering Efficiency Class	D
Air Flow at minimum speed	235 m ³ /h
Air flow at maximum speed	574 m ³ /h
Air flow at boost speed	626 m ³ /h
Airbourne acoustical A-weighted sound Power Emission at minimum speed	48 dBA
Airborne acoustical A-weighted sound Power Emission at maximum speed	69 dBA
Airbourne acoustical A-weighted sound power emission at boost speed	70 dBA
Power consumption in stand-by mode	0.49 W
Time increase factor	1.0
Energie-efficiëntie-index	57
Measured air flow rate at best efficiency point	308 m ³ /h
Measured air pressure at best efficiency point	448 Pa
Measured electric power input at best efficiency point	132 W
Normal Power of the light system	5 W
Gemiddelde lichtsterkte van het licht op het kookoppervlak (Emiddle)	361 lux
Sound power level at highest setting	69 dBA

dinsdag 9 juni 2026
