

**Productkaart volgens de Gedelegeerde Verordening (EU) nr. 65/2014 van de Commissie van 1 oktober 2013 en de Gedelegeerde Verordening (EU) nr. 66/2014 van de Commissie van 14 januari 2014**

---

Naam of handelsmerk van de leverancier	SMEG
Productcode	KSGT74X
Jaarlijks energieverbruik (AEChood)	47.8 kWh/a
Energy efficiency class	A
Fluid Dynamic Efficiency (FDEhood)	30.3
Fluid Dynamic Efficiency class	A
Lighting Efficiency (LEhood)	42.6 lux/W
Lighting Efficiency Class	A
Grease Filtering Efficiency	87.2 %
Grease Filtering Efficiency Class	B
Air Flow at minimum speed	254 m <sup>3</sup> /h
Air flow at maximum speed	603 m <sup>3</sup> /h
Air flow at boost speed	657 m <sup>3</sup> /h
Airbourne acoustical A-weighted sound Power Emission at minimum speed	48 dBA
Airborne acoustical A-weighted sound Power Emission at maximum speed	69 dBA
Airbourne acoustical A-weighted sound power emission at boost speed	70 dBA
Power consumption in stand-by mode	0.49 W
Time increase factor	0.9
Energie-efficiëntie-index	51.8
Measured air flow rate at best efficiency point	329 m <sup>3</sup> /h
Measured air pressure at best efficiency point	448 Pa
Measured electric power input at best efficiency point	135 W
Normal Power of the light system	5 W
Gemiddelde lichtsterkte van het licht op het kookoppervlak (Emiddle)	196 lux
Sound power level at highest setting	69 dBA

den 14 maj 2026

---