

Supplier name or brand	SMEG
Product code	KT110BLE
Annual Efficiency Consumption (AEC _{hood})	56.9 kWh/a
Energy efficiency class	A
Fluid Dynamic Efficiency (FDE _{hood})	31.1
Fluid Dynamic Efficiency class	A
Lighting Efficiency (LE _{hood})	83.2 lux/W
Lighting Efficiency Class	A
Grease Filtering Efficiency	69.2 %
Grease Filtering Efficiency Class	D
Air Flow at minimum speed	326 m ³ /h
Air flow at maximum speed	554 m ³ /h
Air flow at boost speed	784 m ³ /h
Airborne acoustical A-weighted sound Power Emission at minimum speed	49 dB(A)
Airborne acoustical A-weighted sound Power Emission at maximum speed	63 dB(A)
Airborne acoustical A-weighted sound power emission at boost speed	71 dB(A)
Time increase factor	1.00
Energy efficiency index	52.2
Measured air flow rate at best efficiency point	413 m ³ /h
Measured air pressure at best efficiency point	456 Pa
Measured electric power input at best efficiency point	168 W
Normal Power of the light system	2 W
Average illumination of the light on the cooking surface (E _{middle})	183 lux
Sound power level at highest setting	63 dB(A)

neděle 4. srpna 2024