

## Product fiche concerning the COMMISSION REGULATION (EU) No 66/2014 of 14 January 2014

Annual Efficiency Consumption (AEChood)  Energy efficiency class  A  Fluid Dynamic Efficiency (FDEhood)  31.1  Fluid Dynamic Efficiency class  A  Lighting Efficiency (LEhood)  B3.2 lux/W  Lighting Efficiency Class  A  Grease Filtering Efficiency  G9.2 %  Grease Filtering Efficiency Class  D  Air Flow at mimimum speed  Air flow at maximum speed  Air flow at boost speed  784 m³/h  Air flow at boost speed  Airbourne acoustical A-weighted sound Power Emission at minimum speed  Airbourne acoustical A-weighted sound power emission at boost speed  71 dBA  Airbourne acoustical A-weighted sound power emission at boost speed  71 dBA  Energy efficiency index  Energy efficiency point  Measured air flow rate at best efficiency point  Measured electric power input at best efficiency point  Measured electric power input at best efficiency point  Normal Power of the light system  A  Aveage illumination of the light on the cooking surface (Emiddle)  83.1.1  A  13.1.1  A  4.1.1  4.1.1  4.1.1  4.1.1  4.2.2  4.3.2  4.3.2  4.3.2  4.3.3  4.3.3  4.4.3  4.4.3  4.4.3  4.5.3  4.5.3  4.5.3  4.5.4  4.5.4  4.5.4  4.5.5  4.5.5  4.5.5  4.5	Supplier name or brand	SMEG
Energy efficiency class  A Fluid Dynamic Efficiency (FDEhood)  31.1  Fluid Dynamic Efficiency class  A Lighting Efficiency (LEhood)  Lighting Efficiency (LEhood)  Lighting Efficiency Class  A Grease Filtering Efficiency  Grease Filtering Efficiency  Grease Filtering Efficiency Class  D Air Flow at minimum speed  326 m³/h  Air flow at maximum speed  554 m³/h  Air flow at boost speed  784 m³/h  Airbourne acoustical A-weighted sound Power Emission at minimum speed  49 dBA  Airbourne acoustical A-weighted sound power emission at boost speed  71 dBA  Energy efficiency index  52.2  Measured air flow rate at best efficiency point  456 Pa  Measured electric power input at best efficiency point  Measured electric power input at best efficiency point  Normal Power of the light system  2 W  Average illumination of the light on the cooking surface (Emiddle)  183 lux	Product code	KT110PE
Fluid Dynamic Efficiency (FDEhood)  31.1  Fluid Dynamic Efficiency class  Lighting Efficiency (LEhood)  Lighting Efficiency (LEhood)  Lighting Efficiency Class  A  Grease Filtering Efficiency  Grease Filtering Efficiency  Grease Filtering Efficiency Class  D  Air Flow at mimimum speed  326 m³/h  Air flow at maximum speed  554 m³/h  Air flow at boost speed  784 m³/h  Airbourne acoustical A-weighted sound Power Emission at minimum speed  49 dBA  Airbourne acoustical A-weighted sound power emission at boost speed  71 dBA  Energy efficiency index  52.2  Measured air flow rate at best efficiency point  Measured air pressure at best efficiency point  Measured electric power input at best efficiency point  Measured electric power input at best efficiency point  Normal Power of the light system  2 W  Average illumination of the light on the cooking surface (Emiddle)	Annual Efficiency Consumption (AEChood)	56.9 kWh/a
Fluid Dynamic Efficiency class  A Lighting Efficiency (LEhood)  Lighting Efficiency Class  A Grease Filtering Efficiency  Grease Filtering Efficiency  Grease Filtering Efficiency Class  Air Flow at mimimum speed  Air flow at maximum speed  Air flow at most boost speed  Air flow at boost speed  Airbourne acoustical A-weighted sound Power Emission at minimum speed  Airbourne acoustical A-weighted sound Power Emission at maximum speed  Airbourne acoustical A-weighted sound Power Emission at boost speed  Airbourne acoustical A-weighted sound Power Emission at boost speed  Airbourne acoustical A-weighted sound Power Emission at boost speed  Airbourne acoustical A-weighted sound power emission at boost speed  TidBA  Energy efficiency index  52.2  Measured air flow rate at best efficiency point  Measured air pressure at best efficiency point  Measured electric power input at best efficiency point  Measured electric power input at best efficiency point  Normal Power of the light system  2 W  Average illumination of the light on the cooking surface (Emiddle)  183 lux	Energy efficieency class	A
Lighting Efficiency (LEhood)  Lighting Efficiency Class  A  Grease Filtering Efficiency  Grease Filtering Efficiency  Grease Filtering Efficiency Class  D  Air Flow at mimimum speed  Air flow at maximum speed  Air flow at boost speed  Air flow at boost speed  Airbourne acoustical A-weighted sound Power Emission at minimum speed  Airbourne acoustical A-weighted sound Power Emission at maximum speed  Airbourne acoustical A-weighted sound power emission at most maximum speed  Airbourne acoustical A-weighted sound power emission at boost speed  71 dBA  Energy efficiency index  52.2  Measured air flow rate at best efficiency point  413 m³/h  Measured air pressure at best efficiency point  456 Pa  Measured electric power input at best efficiency point  168 W  Normal Power of the light system  2 W  Average illumination of the light on the cooking surface (Emiddle)  183 lux	Fluid Dynamic Efficiency (FDEhood)	31.1
Lighting Efficiency Class Grease Filtering Efficiency Grease Filtering Efficiency Class D Air Flow at mimimum speed 326 m³/h Air flow at maximum speed 554 m³/h Air flow at boost speed 784 m³/h Air flow at boost speed 784 m³/h Airbourne acoustical A-weighted sound Power Emission at minimum speed 49 dBA Airbourne acoustical A-weighted sound Power Emission at maximum speed 63 dBA Airbourne acoustical A-weighted sound power emission at boost speed 71 dBA Energy efficiency index 52.2 Measured air flow rate at best efficiency point 413 m³/h Measured air pressure at best efficiency point 456 Pa Measured electric power input at best efficiency point 168 W Normal Power of the light system 2 W Average illumination of the light on the cooking surface (Emiddle) 183 lux	Fluid Dynamic Efficiency class	A
Grease Filtering Efficiency Grease Filtering Efficiency Class D Air Flow at mimimum speed 326 m³/h Air flow at maximum speed 554 m³/h Air flow at boost speed 784 m³/h Airbourne acoustical A-weighted sound Power Emission at minimum speed 49 dBA Airborne acoustical A-weighted sound Power Emission at maximum speed 63 dBA Airbourne acoustical A-weighted sound power emission at boost speed 71 dBA Energy efficiency index 52.2 Measured air flow rate at best efficiency point 413 m³/h Measured air pressure at best efficiency point 456 Pa Measured electric power input at best efficiency point 168 W Normal Power of the light system 2 W Average illumination of the light on the cooking surface (Emiddle) 183 lux	Lighting Efficiency (LEhood)	83.2 lux/W
Grease Filtering Efficiency Class  Air Flow at mimimum speed  Air flow at maximum speed  554 m³/h  Air flow at boost speed  784 m³/h  Air flow at boost speed  784 m³/h  Airbourne acoustical A-weighted sound Power Emission at minimum speed  49 dBA  Airborne acoustical A-weighted sound Power Emission at maximum speed  63 dBA  Airbourne acoustical A-weighted sound power emission at boost speed  71 dBA  Energy efficiency index  52.2  Measured air flow rate at best efficiency point  413 m³/h  Measured air pressure at best efficiency point  456 Pa  Measured electric power input at best efficiency point  168 W  Normal Power of the light system  2 W  Average illumination of the light on the cooking surface (Emiddle)	Lighting Efficiency Class	A
Air Flow at mimimum speed 326 m³/h  Air flow at maximum speed 554 m³/h  Air flow at boost speed 784 m³/h  Air flow at boost speed 49 dBA  Airbourne acoustical A-weighted sound Power Emission at minimum speed 63 dBA  Airbourne acoustical A-weighted sound Power Emission at maximum speed 63 dBA  Airbourne acoustical A-weighted sound power emission at boost speed 71 dBA  Energy efficiency index 52.2  Measured air flow rate at best efficiency point 413 m³/h  Measured air pressure at best efficiency point 456 Pa  Measured electric power input at best efficiency point 168 W  Normal Power of the light system 2 W  Average illumination of the light on the cooking surface (Emiddle) 183 lux	Grease Filtering Efficiency	69.2 %
Air flow at maximum speed 784 m³/h  Air flow at boost speed 784 m³/h  Airbourne acoustical A-weighted sound Power Emission at minimum speed 49 dBA  Airborne acoustical A-weighted sound Power Emission at maximum speed 63 dBA  Airbourne acoustical A-weighted sound power emission at boost speed 71 dBA  Energy efficiency index 52.2  Measured air flow rate at best efficiency point 413 m³/h  Measured air pressure at best efficiency point 456 Pa  Measured electric power input at best efficiency point 168 W  Normal Power of the light system 2 W  Average illumination of the light on the cooking surface (Emiddle) 183 lux	Grease Filtering Efficiency Class	D
Air flow at boost speed  Air flow at boost speed  Airbourne acoustical A-weighted sound Power Emission at minimum speed  Airbourne acoustical A-weighted sound Power Emission at maximum speed  Airbourne acoustical A-weighted sound power emission at boost speed  Airbourne acoustical A-weighted sound power emission at boost speed  Energy efficiency index  52.2  Measured air flow rate at best efficiency point  413 m³/h  Measured air pressure at best efficiency point  456 Pa  Measured electric power input at best efficiency point  168 W  Normal Power of the light system  2 W  Average illumination of the light on the cooking surface (Emiddle)	Air Flow at mimimum speed	326 m³/h
Airbourne acoustical A-weighted sound Power Emission at minimum speed 49 dBA  Airbourne acoustical A-weighted sound Power Emission at maximum speed 63 dBA  Airbourne acoustical A-weighted sound power emission at boost speed 71 dBA  Energy efficiency index 52.2  Measured air flow rate at best efficiency point 413 m³/h  Measured air pressure at best efficiency point 456 Pa  Measured electric power input at best efficiency point 168 W  Normal Power of the light system 2 W  Average illumination of the light on the cooking surface (Emiddle) 183 lux	Air flow at maximum speed	554 m³/h
Airborne acoustical A-weighted sound Power Emission at maximum speed  Airbourne acoustical A-weighted sound power emission at boost speed  71 dBA  Energy efficiency index  52.2  Measured air flow rate at best efficiency point  413 m³/h  Measured air pressure at best efficiency point  456 Pa  Measured electric power input at best efficiency point  168 W  Normal Power of the light system  2 W  Average illumination of the light on the cooking surface (Emiddle)  183 lux	Air flow at boost speed	784 m³/h
Airbourne acoustical A-weighted sound power emission at boost speed  Energy efficiency index  52.2  Measured air flow rate at best efficiency point  Measured air pressure at best efficiency point  456 Pa  Measured electric power input at best efficiency point  Normal Power of the light system  Average illumination of the light on the cooking surface (Emiddle)  71 dBA  52.2  413 m³/h  456 Pa  168 W  183 lux	Airbourne acoustical A-weighted sound Power Emission at minimum speed	49 dBA
Energy efficiency index  52.2  Measured air flow rate at best efficiency point  413 m³/h  Measured air pressure at best efficiency point  456 Pa  Measured electric power input at best efficiency point  168 W  Normal Power of the light system  2 W  Average illumination of the light on the cooking surface (Emiddle)  183 lux	Airborne acoustical A-weighted sound Power Emission at maximum speed	63 dBA
Measured air flow rate at best efficiency point  Measured air pressure at best efficiency point  Measured electric power input at best efficiency point  Measured electric power input at best efficiency point  Normal Power of the light system  2 W  Average illumination of the light on the cooking surface (Emiddle)  183 lux	Airbourne acoustical A-weighted sound power emission at boost speed	71 dBA
Measured air pressure at best efficiency point 456 Pa  Measured electric power input at best efficiency point 168 W  Normal Power of the light system 2 W  Average illumination of the light on the cooking surface (Emiddle) 183 lux	Energy efficiency index	52.2
Measured electric power input at best efficiency point  Normal Power of the light system  2 W  Average illumination of the light on the cooking surface (Emiddle)  183 lux	Measured air flow rate at best efficiency point	413 m³/h
Normal Power of the light system 2 W  Average illumination of the light on the cooking surface (Emiddle) 183 lux	Measured air pressure at best efficiency point	456 Pa
Average illumination of the light on the cooking surface (Emiddle)  183 lux	Measured electric power input at best efficiency point	168 W
	Normal Power of the light system	2 W
Sound power level at highest setting 63 dBA	Average illumination of the light on the cooking surface (Emiddle)	183 lux
	Sound power level at highest setting	63 dBA

Sunday, 3 August 2025