

| | |
|---|-----------------------|
| Supplier name or brand | SMEG |
| Product code | KT90PE |
| Annual Efficiency Consumption (AEC _{hood}) | 59.4 kWh/a |
| Energy efficiency class | A |
| Fluid Dynamic Efficiency (FDE _{hood}) | 30 |
| Fluid Dynamic Efficiency class | A |
| Lighting Efficiency (LE _{hood}) | 102.3 lux/W |
| Lighting Efficiency Class | A |
| Grease Filtering Efficiency | 76.6 % |
| Grease Filtering Efficiency Class | C |
| Air Flow at minimum speed | 334 m ³ /h |
| Air flow at maximum speed | 567 m ³ /h |
| Air flow at boost speed | 788 m ³ /h |
| Airbourne acoustical A-weighted sound Power Emission at minimum speed | 49 dBA |
| Airborne acoustical A-weighted sound Power Emission at maximum speed | 61 dBA |
| Airbourne acoustical A-weighted sound power emission at boost speed | 69 dBA |
| Time increase factor | 1.00 |
| Energy efficiency index | 52.4 |
| Measured air flow rate at best efficiency point | 438 m ³ /h |
| Measured air pressure at best efficiency point | 434 Pa |
| Measured electric power input at best efficiency point | 176 W |
| Normal Power of the light system | 2 W |
| Average illumination of the light on the cooking surface (E _{middle}) | 225 lux |
| Sound power level at highest setting | 61 dBA |

pátek 26. června 2026