

LDR102-2

Materiaal	Inox
Type spoelbak	Gesoldeerd/ Gelast
Aantal spoelbakken	1 + 3/4
Verlek	Omkeerbaar
EAN-code	8017709304591



Design



Design	Universeel	Type inbouw	Vlak opbouw
Series	Mira	Logo	In reliëf
Kleur	Inox	Geperforeerde opening voor kraan	2 geperforeerde openingen voor kraan
Afwerking	scotch Brite		

	Type spoelbak	Staaldikte spoelbak (mm)	Afmetingen spoelbak, BxHxD (mm)	Diepte spoelbak (mm)	Hoekradius spoelbak	Overloop spoelbak L	Positie crepine	Afmeting crepine
Spoelbak rechts	Spoelbakje	1	147 x 296 x 150	150	50		Centrale spoelbak	8,89 cm
Spoelbak links	Minimum radius	1	340 x 400 x 200	200	15	Ja, verzonken	Zijkant spoelbak	8,89 cm

Technische specificaties



Frame dikte	0,7 mm	Pop-up bediening	Ja, dubbel
Diepte frame (mm)	15	Type popup bediening	Rond
Afmetingen product (mm)	215x1000x500 mm	Inox tussenstuk spoelbak	30 mm
Afmetingen nis (mm)	980 x 480 mm	Inclinatie verlek	2 °
Hoogte vanaf werkblad	6 mm	Type garnituur	Afdichtpasta
Afmeting inbouwmeubel	80 cm	Aantal haken	8
		Type haken	Standaard

Not included accessories



3713

Siphon double bowls sinks (dishwasher connection included)



CB28QU

Single HPL chopping board for minimum radius, oak, measures 280 x 418 H 12 mm



COL19H

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 100 mm



DB34

St/steel drain basket to fit STD radius 340 x 400 bowl, 180 mm depth



KITFD075

Waste disposal 0,75 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



KITSLTRND2

2 Bowls automatic Rondò pop up waste kit with rectangular overflow and round knob



CB25MN

Single HPE chopping board to fit minimum radius bowls, black matt, measures 250 x 410 H 12 mm, dishwasher safe



COL19

St/Steel colander to fit MINIMUM radius mm bowl, measures 200 x 410 x 26 mm



COL36

St/steel colander for MINIMUM radius bowls, measures 370 x 410 x 30 mm




KITFD050

Waste disposal 0,5 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



KITFD100

Waste disposal 1 HP, Motor: 1/2 horsepower, Fits all sinks with 3 1/2" waste outlet



STABMIX

Tap stabiliser

Symbols glossary



Cupboard width required for sink installation



Sink depth - depending on the model, the depth can be from 13 to 24,5



Sink depth - depending on the model, the depth can be from 13 to 24,5



Ultra-low profile: Installation of product with flat edge - height of 1 mm.



Benefit (TT)

Two bowls

Two bowls for greater versatility and dual functionality

Drainer

The drawer allows dishes, cutlery and kitchen utensils to be placed directly on the sink after washing: excess water can drain into the sink, allowing for natural drying

Double tap hole

The sink is easily reversible, making it possible to create any type of kitchen composition

Pop-up command

The pop-up command allows the sink drain to be opened and closed remotely with a simple gesture and without the need to touch the plug directly, increasing convenience and hygiene in the kitchen

Tap hole

Possibility of having the tap hole for direct installation of the tap on the sink, for a larger and neater surface area