

**Productkaart volgens de Gedelegeerde Verordening (EU) nr. 65/2014 van de Commissie van 1 oktober 2013 en de Gedelegeerde Verordening (EU) nr. 66/2014 van de Commissie van 14 januari 2014**

Naam of handelsmerk van de leverancier	SMEG
Productcode	KLTI12L4X
Jaarlijks energieverbruik (AEChood)	54.8 kWh/a
Energy efficiency class	A
Fluid Dynamic Efficiency (FDEhood)	33.9
Fluid Dynamic Efficiency class	A
Lighting Efficiency (LEhood)	20.3 lux/W
Lighting Efficiency Class	D
Grease Filtering Efficiency	73.2 %
Grease Filtering Efficiency Class	D
Air Flow at minimum speed	220 m <sup>3</sup> /h
Air flow at maximum speed	560 m <sup>3</sup> /h
Air flow at boost speed	739 m <sup>3</sup> /h
Airbourne acoustical A-weighted sound Power Emission at minimum speed	43 dBA
Airborne acoustical A-weighted sound Power Emission at maximum speed	66 dBA
Airbourne acoustical A-weighted sound power emission at boost speed	71 dBA
Power Consumption in Off mode	0.49 W
Power consumption in stand-by mode	0.49 W
Energie-efficiëntie-index	51.5
Measured air flow rate at best efficiency point	384 m <sup>3</sup> /h
Measured air pressure at best efficiency point	376 Pa
Measured electric power input at best efficiency point	151 W
Normal Power of the light system	15 W
Gemiddelde lichtsterkte van het licht op het kookoppervlak (Emiddle)	300 lux
Sound power level at highest setting	66 dBA

onsdag 5. februar 2025